


Gobo Light Specification Sheet

Specification Model: RWLTY250-250W-A-7CK70-30D-7T-HS



Electronic Spec.							
Input Voltage	AC220V						
Power Consumption	250W ±10%						
Leakage current	Max 0.7mA						
Down-Lead Specification	3*1mm² rubber wire (L=500mm)						
Control Mode	DMX512 protocol, RDM function, master - slave control mode						
Cables / Connections	3 Core Wire Lead Cable (3x1.0 mm² Power IN) 4 Core Cable with Male/Female Connector (4x0.3 mm² Signal IN/OUT)						
Segment/Channel	9 (Simplified) /11 (Standard) /13 (Entended)						
Note	The light source of this lamp is replaceable and should be replaced by a professional. If the external cable or flexible cord of this lamp is damaged, it should be replaced by a professional.						
LED Data							
LED Brand	OSRAM chips						
Lamp type	Integrated LED light source						
LED Power	120W						
Bulb Life	30000 hours						
Illumination Spec.							
CCT	7000K						
Beam Angle(°)FWHM	30°	45°					
Typical Lumen (lm)	7850 (±10)	8080(±10)					
CRI	≥80						
Function							
Color Plate	7 colors + blank						
Pattern	7 gobos + blank						
Effect	Water ripple effect disc						
Focus	Electric focusing						
Dimmer	0 - 100% dimming, 4 dimming curves, 3 dimming speeds, multiple refresh frequencies available						
Strobe	0 - 25 times per second, two modes: pulse strobing and normal strobing						
Programming	User programs can be edited and saved.						
Mechanical Info.							
Body	ADC12						
Cover	Glass						
Color	Black						
Rotation angle	360°						
Dimension	233mmx297mmx297mm						
Net Weight	8.3kg						
Lens Material	Glass						
Operation Condition							
Oper.Temp.	-20°C ~ +45°C						
Warranty period	3 years						
Testing and certification							
IP Rating	IP66						
Certification Listings	CE, RoHS						
Illuminance Graph							
DIS.	30°	45°					
1m	0.54 15600	0.80 18800					
2m	1.08 8900	1.61 3950					
3m	1.62 3956	2.41 1756					
4m	2.15 2225	3.22 988					
5m	2.69 1424	4.02 632					
6m	3.23 989	4.82 439					
			DIAMETER(M) LUX				