

GOLF-RPW01



DMX1

-40~+45°C


3000K

IP67

IK10

DC
24V

OPTIC OPTIONS



SPECIFICATIONS AVAILABLE FOR RPW01



Sample Part Number: RPW011-1W-1K-K30-D24-110X20D-CL-N-N-HS

FIXTURE TYPE	WATTAGE	LEDS	CCT.	INPUT VOLTAGE	BEAM ANGLE	CONTROL	ANTI-GLARE ACCESSORIES	BRACKET	OPTIONS/ CUSTOMIZATION*
RPW011	1W	1K	K27	D24	110x20D	CL	N	N	HS
RPW011	1W 3W	1K LEDs x1	K30 3000K RGBWH RGBW 4in1 (3W/9W only)	D24 24VDC	110x20D 110x20° 30D 30°	CL On-Off DMX DMX1	N None	N None	HS RAL9001 RAL# Custom RAL#
RPW012	6W 9W	3K LEDs x3							



SPECIFICATION

ELECTRICAL	Input Voltage	24VDC	
	Typical Power Consumption	Max.1W ±10% Max.3W ±10% (@RPW011); Max.6W ±10% Max.9W ±10% (@RPW012)	
OPTICAL	Light Source	High Power LED	
	Color Variants	Mono: 3000K (Ra.>70)	
		Color: RGBW(4in1)	
	Beam Angle (FWHM)	Mono: 110x20° 30°(LEDs x1, LEDs x3)	
		RGBW(4in1): 110x20° 30°(LEDs x1, LEDs x3)	
	Efficacy (lm/W)	Mono: 50~60 (±10%)	
CONTROL	Power Supply	Integrated	
	Operating Modes	On-Off; DMX	
	Control System	DMX512 Controllers	
	Settings / Addressing	DMX Communicator	
PHYSICAL	Length x Width x Height Weight	104mm(L) x 104mm(W) x 35mm(H) 0.3kg @RPW011	
		143mm(L) x 143mm(W) x 45mm(H) 0.5kg @RPW012	
	Housing	Body: Die-cast Aluminum ADC12	
		Cover: Tempered Glass	
	Finish Options	Standard Color	Graphite Black RAL 9011
		Cost Option	Custom RAL #
	Cables / Connections	ON/OFF	DMX
		2 Core Cable with Male/Female Connector (2x1.0 mm ² Cable Power IN/OUT)	5 Core Cable with Male/Female Connector (2x1.0 mm ² Power + 3x0.3 mm ² Signal IN/OUT)
	Mounting Method	Surface Mounting	
	Adjustable	No	
	Protection Factor	Class III	
	IP IK Rating	IP67 IK10	
	Operating Ambient Temperature	-40°C ~ +50°C	
CERTIFICATION	Listings		

Beam Angle (FWHM): 30°



@RPW011



@RPW012