

GOLF-RGD102



OPTIC OPTIONS



90°



SPECIFICATIONS AVAILABLE FOR RGD102

Sample Part Number: RGD102-6W-6K+18K-BD+K27-A-90D-N-N-N-HS


FIXTURE TYPE	WATTAGE	LEDS	CCT.	INPUT VOLTAGE	BEAM ANGLE	CONTROL	ANTI-GLARE ACCESSORIES	BRACKET	OPTIONS/ CUSTOMIZATION*
RGD102	6W	6K+18K	BD+27K	A	120+120D	N	N	N	HS
RGD102	4.5+13.5W	6K+18K LEDs x6 + LEDsX18	BD+K27 2700K BD+K30 3000K BD+K40 4000K BD+K50 5000K BD+K57 5700K	A 220VAC	120+120D 120°+120° 120+90D 120°+90°	CL On-Off DMX DMX	N None	N None	HS Graphite Black RAL 9011 RAL# Custom RAL#
	3+9W					CL On-Off			

SPECIFICATION

ELECTRICAL	Input Voltage	220VAC(Build-in LED driver); 24VDC (External PSU, build-in LED driver)	
	Typical Power Consumption	Max.4.5+13.5W ±10% Max.3+9W ±10%	
OPTICAL	Light Source	High Power LED	
	Color Variants	Mono: 2700K 3000K 4000K 5000K 5700K +Royal Blue	
	Beam Angle (FWHM)	120° +120° (LEDs x6+LEDs x18) 120° +90° (LEDs x6+LEDs x18)	
	Efficacy (lm/W)	50 (±10%)	
CONTROL	Power Supply	Integrated	
	Operating Modes	On-Off	
PHYSICAL	Length x Width x Height Weight	150mm x150mm x350mm 1.4kg	
	Housing	Body: Die-Cast Aluminum ADC12	
		Cover: Tempered Glass	
	Finish Options	Standard Color	Graphite Black RAL 9011
		Cost Option	Custom RAL #
	Cables / Connections	ON/OFF	
		3 Core Wire Lead Cable (3x1.0 mm² Cable Power IN)	
		Mounting Method	
		Spike	
		Adjustable	
		No	
		Protection Factor	
		Class I	
	IP IK Rating	IP66 IK06	
	Operating Ambient Temperature	-40°C ~ +45°C	
CERTIFICATION	Listings	CE, RoHS	

PHOTOMETRIC DATA

Beam Angle (FWHM): 120°



DIMENSIONS

