

GOLF-RGD201



OPTIC OPTIONS



90°



SPECIFICATIONS AVAILABLE FOR RGD201

Sample Part Number: RGD201-0.5W-18K-K27-N-90D-N-N-N-HS


FIXTURE TYPE	WATTAGE	LEDS	CCT.	INPUT VOLTAGE	BEAM ANGLE	CONTROL	ANTI-GLARE ACCESSORIES	BRACKET	OPTIONS/ CUSTOMIZATION*
RGD201	0.5W	18K	27K	N	90D	N	N	N	HS
RGD201	0.5W	18K LEDs x18	K27 2700K K30 3000K K40 4000K K50 5000K K57 5700K	N None	90D 90°	N On-Off	N None	N None	HS Graphite Black RAL 9011 RAL# Custom RAL#

SPECIFICATION

ELECTRICAL	Input Voltage	None (Solar Powered)	
	Typical Power Consumption	Max.0.5W ±10%	
OPTICAL	Light Source	High Power LED	
	Color Variants	Mono: 2700K 3000K 4000K 5000K 5700K	
	Beam Angle (FWHM)	90° (LEDs x18)	
	Efficacy (lm/W)	50 (±10%)	
CONTROL	Power Supply	Integrated	
	Operating Modes	On-Off	
PHYSICAL	Length x Width x Height Weight	276mm x 276mm x 634mm 2.1kg	
	Housing	Body: PC	
		Cover: Tempered Glass	
	Finish Options	Standard Color	Graphite Black RAL 9011
		Cost Option	Custom RAL #
	Cables / Connections	ON/OFF	
		None	
	Mounting Method	Surface Mounting	
	Adjustable	No	
	Protection Factor	None	
	IP IK Rating	IP66 IK06	
	Operating Ambient Temperature	-40°C ~ +45°C	
CERTIFICATION	Listings	CE, RoHS	

PHOTOMETRIC DATA

Beam Angle (FWHM): 90°



DIMENSIONS

