

SPECIFICATION SHEET
INGROUND LIGHT





GOLF - RGL265



DMX 512, -40 ~ +55°C, 2700-6500K, IP67, IK10, DC 24V, AC 100-240V, and various safety and certification icons.

OPTIC OPTIONS ACCESSORIES



Bullseye Louvre(Y9) Honeycomb Louvre (Y2)

SPECIFICATIONS AVAILABLE FOR RGL265

Sample Part Number: RGL265-30W-18K-K27-D24-8D-CL-Y2-N-RAL#

FIXTURE TYPE	WATTAGE	LEDS	CCT.	INPUT VOLTAGE	BEAM ANGLE	CONTROL	ANTI-GLARE ACCESSORIES	BRACKET	OPTIONS/CUSTOMIZATION*
RGL265	30W 36W	18K 18K LEDs x18 24K LEDs x24	K27 K30 K40 K57 K65	D24 D24 24VDC A 220VAC	8D 8D 8° 15D 15° 30D 30° 45D 45° 60D 60° 15x60D 15x60° 20x40D 20x40°	CL CL On-Off DMX DMX512	Y2 Y2 Honeycomb Louvre Y9 Bullseye Louvre	N N N/A	RAL# RAL# Custom RAL#
			RGBWH RGBW(4in1)		15D 15° 30D 30° 45D 45° 60D 60° 15x60D 15x60° 20x40D 20x40°				


SPECIFICATION SHEET

INGROUND LIGHT



SPECIFICATION			
ELECTRICAL	Input Voltage	24VDC (External PSU, build-in LED driver) 220VAC(Build-in LED driver)	
	Typical Power Consumption	30W ±10%	36W ±10%
		24W ±10% (@Ta. 55°C)	30W ±10% (@Ta. 55°C)
OPTICAL	Light Source	High Power LED	
	Color Variants	Mono: 2700K 3000K 4000K Ra.≥80 (R9≥0); 5700K 6500K Ra.≥70 (R9≥0) (SDCM≤7)	
		Color: RGBW(4in1)	
	Beam Angle (FWHM)	Mono: 8° 15° 30° 45° 60° 15x60° 20x40° (LEDs x18, LEDs x24)	
		Color: RGBW(4in1) - 15° 30° 45° 60° 15x60° 20x40° (LEDs x18, LEDs x24)	
CONTROL	Efficiency (lm/W)	Mono: 41; Color: 27 (±10%)	
	Operating Modes	On-Off; DMX	
	Control System	DMX512 Controllers	
	Settings / Addressing	DMX Communicator	
PHYSICAL	Width x Height x Depth Weight	260mm(L) x 260mm(W) x119mm (H) 3.8kg	
	Housing	Body: Die Casting ADC12	
		Cover: Tempered Glass	
	Finish Options	Standard Color	Graphite Black RAL 9011
		Cost Option	Custom RAL #
	Optical Material	PC	Mono: 8°
			RGBW(4in1): 15/30/45/60/20*40/15*60°
		PMMA	Mono: 15/30/45/60/20*40/15*60°
	Cables / Connections	ON / OFF	DMX
		2 Core Cable with Male/Female Connector (2x1mm² Cable Power IN/OUT)	5 Core Cable with Male/Female Connector (2x1mm² Power + 3x0.3 mm² Signal IN/OUT)
		External Mounting Sleeve	
		Adjustable	
		No	
		Protection Factor	
		AC Class I; DC Class III	
		IP IK Rating	
		IP67 IK10	
CERTIFICATION	Operating Ambient Temperature	-40°C ~ +45°C	
	Listings	CE, RoHS	-40°C ~ +55°C(For Mid-East Area)
ACCESSORIES	Not Included Items	Anti-glare Parts (Code)	
	Honeycomb Louvre	Y2	
	Bullseye Louvre	Y9	

PHOTOMETRIC DATA



DIMENSIONS

