

## GOLF-RWL101



### OPTIC OPTIONS



120°



### SPECIFICATIONS AVAILABLE FOR RWL101

Sample Part Number: **RWL101-6W-1K+18K-K27-A-120D-CL-N-N-HS**


| FIXTURE TYPE | WATTAGE   | LEDS              | CCT.        | INPUT VOLTAGE | BEAM ANGLE | CONTROL              | ANTI-GLARE ACCESSORIES | BRACKET | OPTIONS/ CUSTOMIZATION*    |
|--------------|-----------|-------------------|-------------|---------------|------------|----------------------|------------------------|---------|----------------------------|
| RWL101       | 3+15W     | 1K+18K            | K27         | A             | 120D+120D  | CL                   | N                      | N       | HS                         |
| RWL101       | 3+15W     | 1K+18K            | K27 2700K   | A<br>220VAC   | 30D+120D   | CL On-Off            | N None                 | N None  | HS Graphite Black RAL 9011 |
|              |           | LEDs x1 + LEDsx18 | K30 3000K   | D24<br>24VDC  | 30°+120°   |                      |                        |         | RAL# Custom RAL#           |
|              | 2+10W     |                   | K40 4000K   |               |            |                      |                        |         |                            |
|              |           |                   | K50 5000K   |               |            |                      |                        |         |                            |
|              | 1+5W      |                   | K57 5700K   |               |            |                      |                        |         |                            |
|              |           |                   | +Royal Blue |               |            |                      |                        |         |                            |
|              | 3+9W      | 6K+18K            |             |               | 120D+120D  |                      |                        |         |                            |
|              |           | LEDs x6 + LEDsx18 |             |               | 120°+120°  |                      |                        |         |                            |
|              | 4.5+13.5W |                   |             |               |            | CL On-Off<br>DMX DMX |                        |         |                            |

SPECIFICATION

|               |                                 |                                                                                       |                                                                                                             |
|---------------|---------------------------------|---------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| ELECTRICAL    | Input Voltage                   | 220VAC (Build-in LED driver) 24VDC (External PSU, build-in LED driver)                |                                                                                                             |
|               | Typical Power Consumption       | Max.3+15W ±10%   Max.2+10W ±10%   Max.1+5W ±10%<br>Max.4.5+13.5W ±10%   Max.3+9W ±10% |                                                                                                             |
| OPTICAL       | Light Source                    | High Power LED                                                                        |                                                                                                             |
|               | Color Variants                  | Mono: 2700K   3000K   4000K   5000K   5700K +Royal Blue                               |                                                                                                             |
|               | Beam Angle (FWHM)               | 30° + 120° (LEDs x1+LEDs x18)<br>120° + 120° (LEDs x6+LEDs x18)                       |                                                                                                             |
|               | Efficacy (lm/W)                 | 50 (±10%)                                                                             |                                                                                                             |
| CONTROL       | Operating Modes                 | On-Off/ DMX512                                                                        |                                                                                                             |
| PHYSICAL      | Width x Height x Depth   Weight | 150mm (L) x150mm (W) x324mm(H)  1.15kg                                                |                                                                                                             |
|               | Housing                         | Body: Die-Cast Aluminum ADC12                                                         |                                                                                                             |
|               |                                 | Cover: Tempered Glass                                                                 |                                                                                                             |
|               | Optical Material                | PC                                                                                    |                                                                                                             |
|               | Finish Options                  | Standard Color                                                                        | Graphite Black RAL 9011                                                                                     |
|               |                                 | Cost Option                                                                           | Custom RAL #                                                                                                |
|               | Cables / Connections            | ON/OFF                                                                                | DMX512                                                                                                      |
|               |                                 | 3 Core Wire Lead Cable<br>(3x1.0 mm <sup>2</sup> Cable Power IN)                      | 5 Core Cable with Male/Female Connector<br>(2x1mm <sup>2</sup> Power + 3x0.3 mm <sup>2</sup> Signal IN/OUT) |
|               | Mounting Method                 | Surface Mounting                                                                      |                                                                                                             |
|               | Adjustable                      | None                                                                                  |                                                                                                             |
|               | Protection Factor               | Class I                                                                               |                                                                                                             |
|               | IP   IK Rating                  | IP66   IK06                                                                           |                                                                                                             |
|               | Operating Ambient Temperature   | -40°C ~ +45°C                                                                         |                                                                                                             |
| CERTIFICATION | Listings                        | CE, RoHS                                                                              |                                                                                                             |

PHOTOMETRIC DATA

Beam Angle (FWHM): 120°



DIMENSIONS

