

GOLF-RWL102



OPTIC OPTIONS



90°



SPECIFICATIONS AVAILABLE FOR RWL102

Sample Part Number: **RWL102-6W-6K+18K-K27-A-90D-CL-N-N-HS**


FIXTURE TYPE	WATTAGE	LEDS	CCT.	INPUT VOLTAGE	BEAM ANGLE	CONTROL	ANTI-GLARE ACCESSORIES	BRACKET	OPTIONS/ CUSTOMIZATION*
RWL102	6W	6K+18K	K27	A	90D	CL	N	N	HS
	4.5+13.5W	6K+18K LEDs x6 + LEDsx18	K27 2700K K30 3000K K40 4000K K50 5000K K57 5700K +Royal Blue	A 220VAC D24 24VDC	90D 90°	CL On-Off DMX DMX	N None	N None	HS Graphite Black RAL 9011 RAL# Custom RAL#
	3+9W					CL On-Off			

SPECIFICATION

ELECTRICAL	Input Voltage	220VAC(Build-in LED driver); 24VDC (External PSU, build-in LED driver)	
	Typical Power Consumption	Max.4.5+13.5W ±10% Max.3+9W ±10%	
OPTICAL	Light Source	High Power LED	
	Color Variants	Mono: 2700K 3000K 4000K 5000K 5700K +Royal Blue	
	Beam Angle (FWHM)	120° +120° (LEDs x6+LEDs x18) 120° +90° (LEDs x6+LEDs x18)	
	Efficacy (lm/W)	50 (±10%)	
CONTROL	Operating Modes	On-Off/ DMX512	
PHYSICAL	Width x Height x Depth Weight	150mm (L) x150mm (W) x132mm(H) 0.95kg	
	Housing	Body: Die-Cast Aluminum ADC12	
		Cover: Tempered Glass	
	Optical Material	PC	
	Finish Options	Standard Color	Graphite Black RAL 9011
		Cost Option	Custom RAL #
	Cables / Connections	ON/OFF	DMX512
		3 Core Wire Lead Cable (3x1.0 mm² Cable Power IN)	5 Core Cable with Male/Female Connector (2x1mm² Power + 3x0.3 mm² Signal IN/OUT)
	Mounting Method	Surface Mounting	
	Adjustable	No	
	Protection Factor	Class I	
	IP IK Rating	IP66 IK06	
	Operating Ambient Temperature	-40°C ~ +45°C	
CERTIFICATION	Listings	CE, RoHS	

PHOTOMETRIC DATA

Beam Angle (FWHM): 90°



DIMENSIONS

