



Wash Light Specification Sheet

Specification Model:

RWLRS190R-36W-A-RGBW-PK70-15D-N-HS


Electronic Spec.

Input Voltage	176V ~ 264V AC, 50Hz/60Hz
Power Consumption	36W ±10%
Control Mode	DMX512/RDM
Cables / Connections	3 Core Wire Lead Cable (3x1.0 mm ² Power IN) 4 Core Cable with Male/Female Connector (4x0.3 mm ² Signal IN/OUT)
Segment/Channel	11CH channel standard mode / HSV mode

LED Data

LED Brand	OSRAM
LEDs	18 × R/G/B/W (R/G/B/L, R/G/B/A optional)
LED Lifetime	50000 hours

Illumination Spec.

CCT	1800K ~ 7000K color temperature adjustable linearly			
Beam Angle(°)FWHM	15°	25°	30°	45°
Lumen Output	1980lm	1980lm	1980lm	1980lm
Strobing	1-25Hz rapid strobe, with pulse strobe function			
Adjust the Brightness	0~100% smooth linear dimming			

Mechanical Info.

Body	Die casting aluminum
Color	Black
Rotation angle	180°
Dimension	211*154*247mm
Net Weight	4Kg

Operation Condition

Oper.Temp.	-20°C~45°C
Warranty period	3 years

Testing and certification

IP Rating	IP66
IK Rating	IK06
Certification Listing	CE, RoHS

Note

Installation in the Middle East	When installing, space for heat dissipation and ventilation should be reserved (at least 10 cm on each side and the rear). The operating limit can be set through DMX channel configuration or RDM remote control.
---------------------------------	--