


Gobo Light Specification Sheet

Specification Model: RWLTY350-350W-A-7CK70-30D-7T-HS



Electronic Spec.

Input Voltage	AC220V
Power Consumption	350W ±10%
Leakage current	Max 0.7mA
Down-Lead Specification	3*1mm ² rubber wire (L=500mm)
Control Mode	DMX 512 protocol, RDM function, master - slave control mode
Cables / Connections	3 Core Wire Lead Cable (3x1.0 mm ² Power IN) 4 Core Cable with Male/Female Connector (4x0.3 mm ² Signal IN/OUT)
Segment/Channel	9 (Simplified) /11 (Standard) /13 (Extended)
Note	The light source of this lamp is replaceable and should be replaced by a professional. If the external cable or flexible cord of this lamp is damaged, it should be replaced by a professional.

LED Data

LED Brand	OSRAM chips
Lamp type	Integrated LED light source
LED Power	120W
Bulb Life	30000 hours

Illumination Spec.

CCT	7000K							
Beam Angle(°)FWHM	30°	45°						
Typical Lumen (lm)	10030 (±10)	10350 (±10)						
CRI	≥80							

Function

Color Plate	7 colors + blank
Pattern	7 gobos + blank
Effect	Water ripple effect disc
Focus	Electric focusing
Dimmer	0 - 100% dimming, 4 dimming curves, 3 dimming speeds, multiple refresh frequencies available
Strobe	0 - 25 times per second, two modes: pulse strobing and normal strobing
Programming	User programs can be edited and saved.

Mechanical Info.

Body	ADC12
Cover	Glass
Color	Black
Rotation angle	360°
Dimension	233mmx297mmx297mm
Net Weight	8.3kg
Lens Material	Glass

Operation Condition

Oper.Temp.	-20°C ~ +45°C
Warranty period	3 years

Testing and certification

IP Rating	IP66
Certification Listings	CE, RoHS

Illuminance Graph

