


## ( WATERWAVE )Water Effect Light Specification Sheet

### Specification Model:

**RWLXG250-250W-A-7CK85-30D-2TSW-HS**



## Electronic Spec.

|                         |                                                                                                                                                                                                 |
|-------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input Voltage           | AC220V                                                                                                                                                                                          |
| Power Consumption       | 250W ±10%                                                                                                                                                                                       |
| Down-Lead Specification | 3*1mm <sup>2</sup> rubber wire (L=500mm)                                                                                                                                                        |
| Control Mode            | DMX 512 protocol, RDM function, master - slave control mode                                                                                                                                     |
| Cables / Connections    | 3 Core Wire Lead Cable (3x1.0 mm <sup>2</sup> Power IN)<br>4 Core Cable with Male/Female Connector (4x0.3 mm <sup>2</sup> Signal IN/OUT)                                                        |
| Segment/Channel         | 7 (Simplified) /8 (Standard) /10 (Entended)                                                                                                                                                     |
| Note                    | The light source of this lamp is replaceable and should be replaced by a professional. If the external cable or flexible cord of this lamp is damaged, it should be replaced by a professional. |

## LED Data

|           |                             |
|-----------|-----------------------------|
| LED Brand | OSRAM chips                 |
| Lamp type | Integrated LED light source |
| LED Power | 200W                        |
| Bulb Life | 30000 hours                 |

## Illumination Spec.

|                       |           |     |  |  |  |  |  |  |
|-----------------------|-----------|-----|--|--|--|--|--|--|
| CCT                   | 8500K     |     |  |  |  |  |  |  |
| Beam Angle(°)FWHM     | 30°       | 45° |  |  |  |  |  |  |
| Light Efficacy (lm/w) | 18 (±10%) |     |  |  |  |  |  |  |
| CRI                   | ≥70       |     |  |  |  |  |  |  |

## Function

|             |                                                                                              |
|-------------|----------------------------------------------------------------------------------------------|
| Color Plate | 7 colors + blank                                                                             |
| Effect      | 2 water ripple effect disc, forward and reverse rotation                                     |
| Focus       | Electric focusing                                                                            |
| Dimmer      | 0 - 100% dimming, 4 dimming curves, 3 dimming speeds, multiple refresh frequencies available |
| Strobe      | 0 - 25 times per second, two modes: pulse strobing and normal strobing                       |
| Programming | User programs can be edited and saved.                                                       |

## Mechanical Info.

|                |                   |
|----------------|-------------------|
| Body           | ADC12             |
| Cover          | Glass             |
| Color          | Black             |
| Rotation angle | 360°              |
| Dimension      | 233mmx297mmx297mm |
| Net Weight     | 8.2kg             |
| Lens Material  | Glass             |

### Operation Condition

|                 |               |
|-----------------|---------------|
| Oper.Temp.      | -20°C ~ +45°C |
| Warranty period | 3 years       |

## Testing and certification

|           |      |
|-----------|------|
| IP Rating | IP66 |
| IK Rating | IK06 |