ROIODS





global.roleds.com

HQ Add.:4F, No.99 Xiangyuan Rd., Gongshu Dist., Hangzhou, Zhejiang, 310015 China Factory Add.: No.3, Hengxin Str., Linping Dist., Hangzhou, Zhejiang, 330113 China T: + 86 571 8610 6001 🌼 : roleds

Smart Pole Modular Smart Pole

SMART LIGHT POLE

MODULAR SMART POLE

The ROLEDS Modular Smart Pole moves away from traditional fixed designs by adopting an innovative modular approach with customizable, segmented structures. This flexibility allows for the selection of functional modules tailored to various applications. The smart pole supports a variety of smart equipment mounts, including lighting, security cameras, IP broadcasts, emergency calls, wireless chargers, solar panels, Wi-Fi, and more— all integrated into a standardized modular system. Modules are connected using a "mortise and tenon joint" structure, ensuring both a cohesive appearance and structural stability.

This design allows for easy customization, enabling the free combination or replacement of modules to meet specific project requirements. Whether for integrating smart equipment or adapting the structure, the modular system delivers both functionality and aesthetic consistency.

Rolens / roleds.com

Intelligent lighting: support a variety of light distribution mode Atmosphere light: support a variety of color customization WIFI: Mobile wifi network access Emergency call: emergency call, visual two-way intercom Intelligent electrical module: intelligent power supply and network transmission


Monitor:

support monitoring area intrusion, fence crossing, item leaving and moving, rapid movement,parking detection; personnel gathering, etc

IP broadcast: support background music playback, directional broadcast

Wireless charging: mobile phones wireless charging







Lighting module

Module size: φ 219 * 480 Power: 20W-50W Color temperature: 3000K-5000K Light distribution 1: PC cover soft light illumination Light distribution 2: coaxial lens with reflector



AP module

Module size: φ219*480 (Min); Power: 15W Power supply: POE, 12V-53.5VDC power supply; WIFI:2.4G/5G Dual-frequency, 1900M Protection level: IP65;



Monitoring module

Size: \(\phi 219 * 340 \) (Min)
Power: 15W
Power supply: POE, DC12V
A 2-inch 4 million intelligent network
ball machine
Protection level: IP66



Broadcast module

Module size: φ 219 * 500 (Min) Power: 30W, 40W Power supply: DC24V IP broadcast: Support for audio format MP3/WMA/FLAC/AAC/WAV



Photovoltaic module

Module size: φ219 * 1200 (min) Power: 120 WP, 150 WP Flexible solar photovoltaic modules, with a conversion rate of 15% Height of 1.5 m. 1.2 m is optional



Projection light

Module size: φ219*480 (min) Power: 35W Projection light / pattern light module, single pattern piece Protection level: IP65



Flood light

Module size: φ 219 * 480 (min) Power: 18-24W Power supply: DC24V, AC220V Flood light module Select high light efficiency LED, with light transmittance of 94% super white glass, to achieve long distance accurate projection. Protection level: IP66





Module connector

Atmosphere light module

Module size: φ219 * 108 + φ219 * 79

The two functional modules are fixed adjacent by the module connection component jacking device, the functional module and the module connection component for special treatment structure waterproof design, and the protection level reaches IP65:Exosible atmosphere light.




Charging pile Alarming Mobile phone charging

Module size: φ 219 * 1200 (min)

The following customization is supported:

- 1. Emergency alarm: built-in installation, built-in 1080P high-definition, ultra-wide Angle camera, diagonal field Angle of 170, single key call, full-duplex intercom, hands-free call.
- 2. Mobile phone charging: support 5V2A wireless charging
- 3. AC charging pile: input 220VAC, output 32A, 7KW, support card swiping, code scanning, embedded installation



Modular Smart Pole Configurations

Smart devices can be customized according to the project needs, such as projection lights, flexible solar panels, LED display screens, etc

	TYPE I	TYPE II	TYPE III	TYPE IV	TYPE V	TYPE VI
Light pole height	3m-6mavailable					
Smart Lighting	360°					
Monitor	√	√	√	_	_	_
Atmosphere Light	√	√	_	√	_	√
IP broadcast	√	_	√	_	_	_
Wireless charging	√	_	√	_	_	_
Emergency call	√	_	√	_	_	√
Solar energy	_	√	_	_	√	_
Flood light	_	_	_	√	_	_
Projection light	_	_	_	_	√	_
LED screen	_	_	_	_	_	√

