



Firefly Light Specification Sheet

Specification Model: RWLYH15-15W-A-W-70D-N-HS



Electronic Spec.

Input Voltage	AC 176V-240V 50/60Hz
Power Consumption	15W $\pm$ 10%
Leakage current	mAX 0.7mA
Down-Lead Specification	3*1mm ² (L=500mm)
Control Mode	ON/OFF, DMX512
Segment/Channel	4

Illumination Spec.

Illuminant	White Laser
Bulb Life	30000Hours
LED power	2W

Function

Color	RGB/Y/B/W
Gobo	500 points arranged irregularly
Effect	Rotation speed and direction are adjustable, and the light spots are arranged irregularly.
Dimmer	0-100% linear dimming, 4 dimming curves, 3 dimming speeds, and multiple refresh frequencies are available.
Strobe	Fast strobing at 1-20 Hz per second, featuring pulse strobing, synchronous and asynchronous strobing effects.
Other	Supports editing and saving of custom user programs.

Mechanical Info.

Body	ADC12
Cover	Glass
Color	Black
Rotation angle	70°/ 90°
Dimension	154mmx155mmx208mm
Net Weight	2.5kg
Lens Material	Glass

Operation Condition

Oper.Temp.	-20°C ~ +50°C
Storage Temp.	-40°C ~ +80°C

Testing and certification

IP Rating	IP66
-----------	------