



RSL10H-L



OPTIC OPTIONS



CONTROL SOCKETS



5/7 pin NEMA Socket New 4-pin Zhaga Socket

SPECIFICATIONS AVAILABLE FOR RSL10H-L

Sample Part Number: RSL10H-L-140W-128K-K27-A-T2-N-N-N-HS

FIXTURE TYPE	WATTAGE	LEDs	CCT.	INPUT VOLTAGE	BEAM ANGLE	CONTROL	ANTI-GLARE ACCESSORIES	BRACKET	OPTIONS/ CUSTOMIZATION*
RSL10H-L	140W	128K	K27	A	T2	N	N	N	HS
RSL10H-L	140W 160W 180W 200W	128K LEDs x 128	K27 2700K K30 3000K K40 4000K K50 5000K K57 5700K	A 220VAC	T2 T2M T3 T3M	N On-Off KKN NEMA Socket KKZ Zhaga Socket	N None	N None	HS Graphite Black RAL9011 RAL# Custom RAL#

SPECIFICATION SHEET

STREET LIGHT




SPECIFICATION


ELECTRICAL	Input Voltage	220VAC	
	Typical Power Consumption	Max.140W ±10% 160W ±10% 180W ±10% 200W ±10%	
OPTICAL	Light Source	High Power LED	
	Color Variants	2700K 3000K 4000K 5000K 5700K Ra.≥70 (SDCM ≤ 7)	
	Beam Angle (FWHM)	T2M T3M	
	Efficacy (lm/W)	145 ±10%	
CONTROL	Power Supply	Integrated (Input Surge Protection: DM6kV, CM10kV)	
	Operating Modes	On-Off; Zigbee, LORA (Options)	
PHYSICAL	Length x Width x Height Weight	606mm x 300mm x 158mm 6kg (*RSL10H-L-200W, 6.4kg)	
	Housing	Body: Die-Casting Aluminum ADC12	
		Cover: Tempered Glass	
	Finish Options	Standard Color	Graphite Black RAL 9011
		Cost Option	Custom RAL #
	Cables / Connections	ON/OFF	
		Cable 3 Wire Lead Cable (3x1.0 mm² Cable Power IN)	
	Mounting Method	Pole Top Mounting Intermediate Fitting	
	Adjustable	±15°	
	Protection Factor	Class I	
	IP IK Rating	IP66 IK08	
	Operating Ambient Temperature	-40°C ~ +55°C	
CERTIFICATION	Listings	CE, CB, ENEC, RoHS	
ACCESSORIES	Optional Items	Control Sockets (Code)	
	5/7 pin Nema Socket	KKN	
	New 4-pin Zhaga Socket	KKZ	

PHOTOMETRIC DATA

Beam Angle (FWHM): T2M



Beam Angle (FWHM): T3M



DIMENSIONS

