


High Power Wash Light Specification Sheet

Specification Model: RWLRS252-1350W-A-RGBWHPK70-L502-8D-HS



Electronic Spec.

Power Consumption	1350W
Input Voltage	200V ~ 277V AC, 50Hz/60Hz
Control Mode	DMX512/RDM
Cables / Connections	3 Core Wire Lead Cable (3x1.0 mm ² Power IN) 4 Core Cable with Male/Female Connector (4x0.3 mm ² Signal IN/OUT)
Segment/Channel	8CH channel standard mode / HSV mode

LED Data

LED	RGBW 4in1 (RGBL optional)
Bulb Life	50000 hours
Lumen	36000
Beam Angle(°)FWHM	8°/15°/25°/30°/45°
Lumen Output	36000lm
CCT	1800K ~ 7000K color temperature adjustable linearly
Dimmer	0 - 100% dimming, 3 dimming speeds, multiple refresh frequencies available
Strobe	1-25Hz regular strobe and pulse strobe

Mechanical Info.

Color	Black (customizable)
Dimension	810*686*583mm
Weight	55kg
Oper.Temp.	-20°C ~ +45°C
Warranty period	3 years

Testing and certification

IP Rating	IP66
IK Rating	IK07
Certification Listing	CE, RoHS

Note

Installation in the Middle East	When installing, space for heat dissipation and ventilation should be reserved (at least 10 cm on each side and the rear). The operating limit can be set through DMX channel configuration or RDM remote control.
---------------------------------	--