


Water Effect Light(Zoom) Specification Sheet

Specification Model: RWLXG350-350W-7CK85-1545D-2TSW-HS



Electronic Spec.

Input Voltage	100V ~ 240V AC, 50Hz/60Hz
Power Consumption	350W ±10%
Leakage current	Max 0.7mA
Down-Lead Specification	3*1mm ² rubber wire (L=500mm)
Control Mode	DMX 512 protocol, RDM function, master - slave control mode
Cables / Connections	3 Core Wire Lead Cable (3x1.0 mm ² Power IN) 4 Core Cable with Male/Female Connector (4x0.3 mm ² Signal IN/OUT)
Segment/Channel	8 (Simplified) /9 (Standard) /12 (Entended)
Note	The light source of this lamp is replaceable and should be replaced by a professional. If the external cable or flexible cord of this lamp is damaged, it should be replaced by a professional.

LED Data

LED Brand	OSRAM chips
Lamp type	Integrated LED light source
LED Power	300W
Bulb Life	30000 hours

Illumination Spec.

CCT	8500K
Beam Angle(°)FWHM	15°-45°
Light Efficacy (lm/w)	18-16 (±10%)
CRI	≥75

Function

Color Plate	7 colors + blank, Rainbow flowing effect
Effect	2 water ripple effect disc, forward and reverse rotation
Focus	Electric focusing
Dimmer	0-100% exponential dimming
Strobe	Electronically Adjustable Speed Strobing (1-25 Hz)
Programming	User programs can be edited and saved.

Mechanical Info.

Body	ADC12
Cover	Glass
Color	Black
Rotation angle	270°
Dimension	233mmx438mmx341mm
Net Weight	12kg
Lens Material	Glass

Operation Condition

Oper.Temp.	-20°C ~ +45°C
Warranty period	3 years

Testing and certification

IP Rating	IP66
IK Rating	IK06