


DaVinci IP66 Projector Specification Sheet

Model: RWLXSD2-230W-B-N-TR1.2-N-HS


Specification

Projection System @Ta. 25°C	Corporate Hospitality & tourism Museums Worship Rental & staging Theme parks & attractions		
		Fixed Lenses	TR: 1.2:1 (Standard)
		Displacement	N/A
		Focus Adjustment Method	Motorized
	Light Source	Light Source Lifespan	≥20,000 hours (Standard Mode)
		Light Source Technology	OSRAM LED
Power Requirements	Power	Normal: 230W;	
	Electrical Rating	AC 100-240V, 50/60Hz @3A	
Display Technology	TI DLP™ Technology, 0.47" DMD		
Brightness	Center: 2000Lm; ANSI: 1900Lm		
Resolution	1,920×1,080P (2,073,600 pixels) (16:9)		
Contrast	TYP.400: 1		
Aspect Ratio	Standard 16:9		
Projection Mode	Tabletop front projection, tabletop rear projection, lifting projection, lifting rear projection		
Projection Size	40 ~ 150 inches		
Uniformity (9 - Point Average)	93%+		
Color Gamut	DCI-P3		
Special Features	Mapping Software System	Included. 4 Directions	
	Picture Engine	9x9 points correction	
	Convenient Mapping Display Mode	Master & Slave mode, Up to 254 sets	
	Remote Management	Devices as a central	
Picture Features	Operation System	Linux	
	Picture Engine	Keystom correction, Geometric correction, Edge blending, Image scaling	
	Color Engine	Splicing color difference adjustment, RGB color convergence, Local brightening, Dark field compensation, Gamma correction,	
Functions	Remote Management	Remote upgrade, maintenance, and management of projection equipment, including video encoding, decoding, transmission, synchronization, etc.	
	Offline Mode	Supported	
	Infrared Remote Control	Supported	
	Video Playback	Supported	
	Interactive Technology	/	
Ports (IP Rated)	Input Ports	HDMI*1 / HDBaseT (RJ45 Ethernet*1)/ Reserved*1 (USB/ IR/ etc.)	
	Output Ports	Audio*1	
	Control Method	RJ45 Ethernet/ Remote control	
PC Spec.	1GB RAM, 8GB Storage +32GB SD Card		
Audible Noise	Standar: 45dBA (Max.)		
Operating Temperature	20 ~ 50°C (power on for preheating 15 minutes in advance lower than -20°C & enter intelligent power mode above 45°C		
Impact Resistance Rating	IK08		
Waterproof Rating	IP66		
Operating Humidity	10% - 85% humidity (non-condensing)		
Storage Temperature	0°C - 85°C, 10% - 80% humidity (non-condensing)		
Dimensions	350mmx321mmx270mm(With bracket)		
Weight	15kg (With Bracket)		
Others			
Power Cord	3 Core Wire Lead		
Remote Control	Standard*1		
RJ45 IP connector	Standard*1		
User Manual	1		
Product Certification	3C Certification, Energy - saving and Environmental Protection Certification, Test Report		
Warranty	2 years		